



# LUBRICATION AND PROCESS PRODUCT GUIDE

MINING & INDUSTRIAL APPLICATIONS

**AUSTRALIA & NEW ZEALAND**

**2024  
EDITION**

**INCLUDES  
QUANTM™ EODD PUMPS**



**PUMPS | METERS | REELS**

PROVEN QUALITY. LEADING TECHNOLOGY.



For complete range refer to the [Vehicle Service Equipment BUYER'S GUIDE \(303245\)](#)

For more information on Graco products and manuals please visit  
[www.graco.com](http://www.graco.com) or contact Customer Service 03 9468 8500 – [csaustralia@graco.com](mailto:csaustralia@graco.com)

# Contents

## **OIL PUMPS**

LD Series™  
Mini Fire-Ball 225  
Fire-Ball® 300  
Fire-Ball® 425  
NXT High-Flo Oil Pumps  
NXT Dura-Flo Oil Pumps  
Oil Pump Packages

## **GREASE PUMPS**

LD™ 50:1  
Mini Fire-Ball® 225  
Fire-Ball® 300  
Fire-Ball® 425  
GT 750  
NXT™ Check-Mate® Grease Pumps  
Grease Pump Packages

## **DISPENSE METERS**

EM® Series Electronic Meters  
PM Electronic Preset Meters  
SD Series™ Electronic Meters  
IM20 In-Line Electronic Meters  
SDV15 Control Valves  
XDV20 Control Valves

## **HOSE REELS**

Hose Reels Overview  
LDX™ Series Hose Reels  
SDX™ Series Hose Reels  
XDX™ Series 10/20 Hose Reels  
XD™ Series 30 Hose Reels  
XD™ Series 40/50 Hose Reels  
XD™ Series 60/70/80  
Power Rewind Hose Reels  
Powered Reels Ordering information

## **ELECTRIC TRANSFER PUMPS**

EGP™ Pumps

## **HUSKY PUMPS**

Husky 205 AODD Pump  
Husky 515 AODD Pump  
Husky 716 AODD Pump  
Husky 1050 AODD Pump  
Husky 1590 AODD Pump  
Husky 2150 AODD Pump  
Husky 3300 AODD Pump

## **QUANTM PUMPS**

Quantm i30 1"  
Quantm i80 1.5"  
Quantm i120 2"



# OIL PUMPS



## Oil Pump Selection Guide

Pump Family and Fluid Pressure Ratio	Typical Applications	Annual Usage	Line Length	Simultaneous Dispense Points	Approx. Free Flow Rate @ 100 psi	Air Inlet	Fluid Inlet	Fluid Outlet	Air Operation Range	Description	Part Number
<b>Fast-Ball, 100, 1:1</b> 	<ul style="list-style-type: none"> <li>Automotive dealerships</li> <li>Fast lube centers</li> <li>Fleet service facilities</li> <li>Heavy-duty dealerships</li> <li>In-plant</li> <li>Lube trucks</li> <li>Lubricant transfer</li> <li>Mining</li> <li>Service shops</li> </ul>	19,00 l (5,000 gal)	30 m (<100 ft)	1 (no reels)	44 lpm (12 gpm)	1/4 NPT(F)	1-1/2 NPT(F) 1 in	3/4 NPT(F) 1 in	40-150 psi (2.7-12.5 bar)	Universal Length Pump 55 Gallon Drum Length Pump	279035 – NSA 279037 – NSA *3a9292
<b>LD, 3:1</b> 	<ul style="list-style-type: none"> <li>Automotive dealerships</li> <li>Fast lube centers</li> <li>Lube trucks</li> <li>Lubricant transfer</li> <li>Service shops</li> </ul>	75,000 l (20,000 gal)	91 m (300 ft)	1 to 2	30 lpm (7.8 gpm)	1/4 NPT(F)	1 NPT(F)	1/2 NPT(F)	20-150 psi (1.37-10.3 bar)	Pump Universal c/w bung adaptor Pump Multilength	24G576 NPT – STK 24G578 BSPT – STK 24G579 NPT – STK *3A1334
<b>LD, 5:1</b> 	<ul style="list-style-type: none"> <li>Automotive dealerships</li> <li>Fast lube centers</li> <li>Lube trucks</li> <li>Lubricant transfer</li> <li>Service shops</li> </ul>	75,000 l (20,000 gal)	91 m (300 ft)	1 to 2	25 lpm (6.7 gpm)	1/4 NPT(F)	1 NPT(F)	1/2 NPT(F)	20-150 psi (1.37-10.3 bar)	Pump Universal c/w bung adaptor Pump Multilength	24G588 NPT – STK 24G590 BSPT – STK 24G591 NPT – STK *3A1334
<b>Mini Fire-Ball 225, 3:1</b> 	<ul style="list-style-type: none"> <li>Automotive dealerships</li> <li>Fast lube centers</li> <li>Fleet service facilities</li> <li>Heavy-duty dealerships</li> <li>In-plant</li> <li>Lube trucks</li> <li>Lubricant transfer</li> <li>Mining</li> <li>Service shops</li> </ul>	113,500 l (30,000 gal)	76 m (250 ft)	1 to 2	32 lpm (8.3 gpm)	3/8 NPT(F)	1-1/2 NPT(F)	1/2 NPT(F)	40-180 psi (2.8-12 bar)	Pump Universal	248097 – STK *309868
<b>Fire-Ball 300, 5:1</b> 	<ul style="list-style-type: none"> <li>Automotive dealerships</li> <li>Fast lube centers</li> <li>Fleet service facilities</li> <li>Heavy-duty dealerships</li> <li>In-plant</li> <li>Lube trucks</li> <li>Lubricant transfer</li> <li>Mining</li> <li>Service shops</li> </ul>	132,000 l (35,000 gal)	152 m (500 ft)	1 to 3	46 lpm (12.1 gpm)	3/8 NPT(F)	1-1/2 NPT(F)	1/2 NPT(F)	40-180 psi (2.8-12 bar)	Universal oil pump Oil pump, 60L (16gal) Oil pump, 200L (55gal) Oil pump, 1040L (275gal)	203876 – STK 203872 – NSA 204254 – STK 222087 – STK *306518
<b>Fire-Ball 425, 3:1</b> 	<ul style="list-style-type: none"> <li>Automotive dealerships</li> <li>Fast lube centers</li> <li>Fleet service facilities</li> <li>Heavy-duty dealerships</li> <li>In-plant</li> <li>Lube trucks</li> <li>Lubricant transfer</li> <li>Mining</li> <li>Service shops</li> </ul>	132,000 l (>35,000 gal)	76 m (Up to 250 ft)	3 to 4	109 lpm (28.7 gpm)	1/2 NPT(F)	1-1/2 NPT(F)	3/4 NPT(F)	40-180 psi (2.8-12 bar)	Universal oil pump	237526 – STK *308485
<b>Fire-Ball 425, 6:1</b> 	<ul style="list-style-type: none"> <li>Automotive dealerships</li> <li>Fast lube centers</li> <li>Fleet service facilities</li> <li>Heavy-duty dealerships</li> <li>In-plant</li> <li>Lube trucks</li> <li>Lubricant transfer</li> <li>Mining</li> <li>Service shops</li> </ul>	132,000 l (>35,000 gal)	152 m (Up to 500 ft)	3 to 4	65 lpm (17.1 gpm)	1/2 NPT(F)	1-1/2 NPT(F)	3/4 NPT(F)	40-180 psi (2.8-12 bar)	Universal oil pump	238108 – STK *308608
<b>Fire-Ball 425, 10:1</b> 	<ul style="list-style-type: none"> <li>Automotive dealerships</li> <li>Fast lube centers</li> <li>Fleet service facilities</li> <li>Heavy-duty dealerships</li> <li>In-plant</li> <li>Lube trucks</li> <li>Lubricant transfer</li> <li>Mining</li> <li>Service shops</li> </ul>	132,000 l (>35,000 gal)	228.6 m (Up to 750 ft)	3 to 4	44 lpm (11.7 gpm)	1/2 NPT(F)	1-1/2 NPT(F)	3/4 NPT(F)	40-180 psi (2.8-12 bar)	Universal oil pump	205626 – STK *308655

\*Manual Number






STK – Normally Stocked item in local warehouse

NSA – Non-stocked item that will be delivered to local warehouse by air freight

NSO – Non-stocked item that will be delivered to local warehouse by ocean freight

Free Flow – Flow rate measured at pump outlet (10w oil)

## Oil Pump Selection Guide

Pump Family and Fluid Pressure Ratio	Typical Applications	Annual Usage	Line Length	Simultaneous Dispense Points	Air Inlet	Fluid Inlet	Fluid Outlet	Air Operation Range	Part Number
<b>NXT High Flo, 3.5:1</b> 	<ul style="list-style-type: none"> <li>Fleet service facilities</li> <li>In-plant large runs</li> <li>Large volume lubricant transfer</li> <li>Mining remote fill</li> </ul>	132,000 l (> 35,000 gal)	76 m (Up to 250 ft)	4 to 5	3/4 NPT(F)	1-1/2 NPT(F)	1 NPT(F)	20-100 psi (1.4-7 bar)	24D602 – NSO *312862
<b>NXT High Flo, 4.5:1</b> 	<ul style="list-style-type: none"> <li>Fleet service facilities</li> <li>In-plant large runs</li> <li>Large volume lubricant transfer</li> <li>Mining remote fill</li> </ul>	132,000 l (> 35,000 gal)	137 m (Up to 450 ft)	4 to 5	3/4 NPT(F)	1-1/2 NPT(F)	1 NPT(F)	20-100 psi (1.4-7 bar)	24D603 – NSO *312862
<b>NXT High Flo, 6:1</b> 	<ul style="list-style-type: none"> <li>Fleet service facilities</li> <li>In-plant large runs</li> <li>Large volume lubricant transfer</li> <li>Mining remote fill</li> </ul>	132,000 l (> 35,000 gal)	152m (Up to 500 ft)	4 to 5	3/4 NPT(F)	1-1/2 NPT(F)	1 NPT(F)	20-75 psi (1.4-5.2 Bar)	CU8231 - NSO *3A3452
<b>NXT Dura-Flo, 6:1</b> 	<ul style="list-style-type: none"> <li>Fleet service facilities</li> <li>In-plant large runs</li> <li>Large volume lubricant transfer</li> <li>Mining remote fill</li> </ul>	132,000 l (> 35,000 gal)	152 m (Up to 500 ft)	2 to 4	3/4 NPT(F)	2 NPT(F)	1-1/2 NPT(F)	20-100 psi (1.4-5.2 bar)	24D604 – NSO *312862
<b>NXT Dura-Flo, 10:1</b> 	<ul style="list-style-type: none"> <li>Fleet service facilities</li> <li>In-plant large runs</li> <li>Large volume lubricant transfer</li> <li>Mining remote fill</li> </ul>	132,000 l (> 35,000 gal)	228.6 m (Up to 750 ft)	2 to 4	3/4 NPT(F)	2 NPT(F)	1-1/2 NPT(F)	20-100 psi (1.4-7 bar)	24D608 – NSO *312862

\*Manual Number

NSA – Non-stocked item that will be delivered to local warehouse by air freight

NSO – Non-stocked item that will be delivered to local warehouse by ocean freight

## Oil Pump Packages

### LDX NPT 3:1 OIL PACKAGES

Standard packages include LDX Series hose reel. Self-relieving air regulator must be used for LD pump thermal relief function. Order regulator 24H420 separately.



Package Number	24H702	24H726	24H751	24H800
Ratio	3:1	3:1	3:1	3:1
Mounting Position	Tote Top	Tote Drain	Cart (with Reel) 200L	Universal
Pump Part Number	24G576 NPT	24G576 NPT	24G576 NPT	24G576 NPT
Suction Tube Size	275 gal (1,040 l)	275 gal (1,040 l)	55 gal (205 l)	55 gal (205 l)
Pump Downtube	16F885		16F886	16F878
Reel Type	LDX	LDX	LDX	
Hose Reel Part Number	HEM004	HEM004	HEM004	
Hose Size	1/2 in x 35 ft	1/2 in x 35 ft	1/2 in x 35 ft	
Reel Bracket Kit	24K285	24K285		
Meter Type	Manual	Manual	Manual	Manual
Meter Part Number	25C903	25C903	25C903	25C903
Meter Extension	Rigid	Rigid	Rigid	Rigid
Hose Kit	6 ft x 3/8 in air hose / 6 ft x 1/2 in fluid hose	6 ft x 3/8 in air hose / 6 ft x 1/2 in fluid hose	6 ft x 3/8 in air hose / 6 ft x 1/2 in fluid hose	6 ft x 3/8 in air hose / 6 ft x 1/2 in fluid hose
Hose Kit Part Number	24J495	24J495	24J495	24H859
Top Mount Tote Bracket	24F930	24F931		
Tote Mount Pump Bracket		24F920		
Meter Tray	24F914	24F914		
Suction Hose Kit		24H669		
Cart			24F915	
Additional Parts			100057 Screw 100527 Washer 111040 Nylock Nut	
Instruction Manual	3A1335	3A1335	3A1335	3A1335

## Oil Pump Packages

### LDX NPT 5:1 OIL PACKAGES

Standard packages include LDX Series hose reel. Self-relieving air regulator must be used for LD pump thermal relief function. Order regulator 24H420 separately.



Package Number	24H868	24H892	24H916	24H965
Ratio	5:1	5:1	5:1	5:1
Mounting Position	Tote Top	Tote Drain	Cart (with Reel) 200L	Universal
Pump Part Number	24G588 NPT	24G588 NPT	24G588 NPT	24G588 NPT
Suction Tube Size	275 gal (1,040 l)	275 gal (1,040 l)	55 gal (205 l)	55 gal (205 l)
Pump Downtube	16F885		16F886	16F878
Reel Type	LDX	LDX	LDX	
Hose Reel Part Number	HEM004	HEM004	HEM004	
Hose Size	1/2 in x 35 ft	1/2 in x 35 ft	1/2 in x 35 ft	
Reel Bracket Kit	24K285	24K285		
Meter Type	Manual	Manual	Manual	Manual
Meter Part Number	25C903	25C903	25C903	25C903
Meter Extension	Rigid	Rigid	Rigid	Rigid
Hose Kit	6 ft x 3/8 in air hose / 6 ft x 1/2 in fluid hose	6 ft x 3/8 in air hose / 6 ft x 1/2 in fluid hose	6 ft x 3/8 in air hose / 6 ft x 1/2 in fluid hose	6 ft x 3/8 in air hose / 6 ft x 1/2 in fluid hose
Hose Kit Part Number	24J495	24J495	24J495	24H859
Top Mount Tote Bracket	24F930	24F931		
Tote Mount Pump Bracket		24F920		
Meter Tray	24F914	24F914		
Suction Hose Kit		24H669		
Cart			24F915	24F915
			100057 Screw 100527 Washer 111040 Nylock Nut	
Instruction Manual	3A1335	3A1335	3A1335	3A1335



# GREASE PUMPS



PART NO. 246781  
SERIAL K01465  
MAX AIR WPR  
1.0 MPa 10 bar 140 psi  
MAX FLUID WPR  
58 MPa 580 bar 8400 psi


SERIES A17D

Made in U.S.A.

Graco Inc.  
P.O. Box 1441  
Mpls., MN 55440-1441 U.S.A.

ARTWORK NO. 292887 REV. C

## Grease Pump Selection Guide

Pump Family and Fluid Pressure Ratio	Typical Applications	Annual Usage	Line Length	Simultaneous Dispense Points	Approx. Free Flow Rate @ 100 psi	Air Inlet	Fluid Outlet	Air Operation Range	Description	Part Number
<b>LD, 50:1</b> 	<ul style="list-style-type: none"> <li>Automotive dealerships</li> <li>Fast lube centers</li> <li>Lube trucks</li> <li>Lubricant transfer</li> <li>Service shops</li> </ul>	3,175 kg (Up to 7,000 lbs)	30.5 m (Up to 100 ft)	1	2 kg/min (4.5 lbs/min)	1/4 in NPT(F)	1/4 in NPT(F)	20-150 psi (1.37-10.3 bar)	16 kg (35 lb) Grease Pump 50:1 55 kg (120 lb) Grease Pump 50:1 180 kg (400 lb) Grease Pump 50:1	24G600 NPT – STK 24G602 BSPT – STK 24G603 NPT – STK 24G605 BSPT – STK 24G606 NPT – STK 24G608 BSPT – STK
<b>Mini Fire-Ball 225, 50:1</b> 	<ul style="list-style-type: none"> <li>Automotive dealerships</li> <li>Fast lube centers</li> <li>Fleet service facilities</li> <li>Heavy-duty dealerships</li> <li>In-plant</li> <li>Lube trucks</li> <li>Lubricant transfer</li> <li>Mining</li> <li>Service shops</li> </ul>	4,535 kg (Up to 10,000 lbs)	30.5 m (Up to 100 ft)	1	0.7 kg/min (1.5 lbs/min)	3/8 in NPT(F)	1/4 in NPT(F)	40-140 psi (2.8-10 bar)	16 kg (35 lb) Grease Pump – 50:1 55 kg (120 lb) Grease Pump – 50:1 180 kg (400 lb) Grease Pump – 50:1	246909 – NSA 246780 – NSA 246781 – NSA *309966
<b>Fire-Ball 300, 15:1</b> 	<ul style="list-style-type: none"> <li>Automotive dealerships</li> <li>Fast lube centers</li> <li>Fleet service facilities</li> <li>Heavy-duty dealerships</li> <li>In-plant</li> <li>Lube trucks</li> <li>Lubricant transfer</li> <li>Mining</li> <li>Service shops</li> </ul>	4,535 kg (Up to 10,000 lbs)	76 m (Up to 250 ft)	1-2	3.4 kg/min (7.5 lbs/min)	3/8 in NPT(F)	1/4 in NPT(F)	40-180 psi (2.8-12.5 bar)	16 kg (35 lb) Grease Pump – 15:1 55 kg (120 lb) Grease Pump – 15:1 180 kg (400 lb) Grease Pump – 15:1	206405 – NSA 206699 – NSA 206700 – STK *306531
<b>Fire-Ball 300, 50:1</b> 	<ul style="list-style-type: none"> <li>Automotive dealerships</li> <li>Fast lube centers</li> <li>Fleet service facilities</li> <li>Heavy-duty dealerships</li> <li>In-plant</li> <li>Lube trucks</li> <li>Lubricant transfer</li> <li>Mining</li> <li>Service shops</li> </ul>	4,535 kg (Up to 10,000 lbs)	76 m (Up to 250 ft)	1-2	3.4 kg/min (7.5 lbs/min)	3/8 in NPT(F)	1/4 in NPT(F)	30-140 psi (2.1-9.7 bar)	16 kg (35 lb) Grease Pump – 50:1 55 kg (120 lb) Grease Pump – 50:1 180 kg (400 lb) Grease Pump – 50:1	239877 – STK 239887 – STK 239888 – STK *308883
<b>Fire-Ball 425, 10:1</b> 	<ul style="list-style-type: none"> <li>Automotive dealerships</li> <li>Fast lube centers</li> <li>Fleet service facilities</li> <li>Heavy-duty dealerships</li> <li>In-plant</li> <li>Lube trucks</li> <li>Lubricant transfer</li> <li>Mining</li> <li>Service shops</li> </ul>	9,072 kg (> 20,000 lbs)	152 m (Up to 500 ft)	4 or more	13.1 kg/min (29 lbs/min)	1/2 in NPT(F)	1 in NPT(F)	40-180 psi (2.8-12.5 bar)	Stubby mount 10:1 pump Fire-Ball 425, 10:1 pump – Includes Bung Adaptor	965124 – STK 965129 – STK *309407
<b>Fire-Ball 425, 50:1</b> 	<ul style="list-style-type: none"> <li>Automotive dealerships</li> <li>Fast lube centers</li> <li>Fleet service facilities</li> <li>Heavy-duty dealerships</li> <li>In-plant</li> <li>Lube trucks</li> <li>Lubricant transfer</li> <li>Mining</li> <li>Service shops</li> </ul>	9,072 kg (> 20,000 lbs)	76 m (Up to 250 ft)	4 or more	4.1 kg/min (9 lbs/min)	1/2 in NPT(F)	3/8 in NPT(F)	40-150 psi (2.8-10.3 bar)	55 kg (120 lb) Grease Pump – 50:1 180 kg (400 lb) Grease Pump – 50:1	205394 – STK 205395 – STK *306674
<b>Fire-Ball 425, 75:1</b> 	<ul style="list-style-type: none"> <li>Automotive dealerships</li> <li>Fast lube centers</li> <li>Fleet service facilities</li> <li>Heavy-duty dealerships</li> <li>In-plant</li> <li>Lube trucks</li> <li>Lubricant transfer</li> <li>Mining</li> <li>Service shops</li> </ul>	9,072 kg (> 20,000 lbs)	152 m (Up to 500 ft)	4 or more	2.9 kg/min (6.5 lbs/min)	1/2 in NPT(F)	3/8 in NPT(F)	40-100 psi (2.8-7 bar)	16 kg (35 lb) Grease Pump – 75:1 55 kg (120 lb) Grease Pump – 75:1 180 kg (400 lb) Grease Pump – 75:1	239731 – NSA 239729 – STK 239730 – NSA *308777
<b>GT 750, 36:1</b> 	<ul style="list-style-type: none"> <li>Fleet service facilities</li> <li>Heavy-duty dealerships</li> <li>In-plant</li> <li>Lube trucks</li> <li>Mining</li> </ul>	9,072 kg (> 20,000 lbs)	76 m (Up to 250 ft)	4 or more	14.5 kg/min (32 lbs/min)	1/2 in NPT(F)	1 in NPT(F)	40-100 psi (2.8-7 bar)	Universal Pump 55 kg (121 lb) 180 kg (400 lb)	24W498 – STK 25D116 – STK 24W337 – STK *3A5363








\*Manual Number

STK – Stocked item in local warehouse

NSA – Non-stocked item that will be delivered to local warehouse by air freight

NSO – Non-stocked item that will be delivered to local warehouse by ocean freight

## Grease Pump Selection Guide

Pump Family and Fluid Pressure Ratio	Typical Applications	Annual Usage	Air Inlet	Fluid Outlet	Air Operation Range	Description	Part Number
<b>Check-Mate 14:1</b> 	<ul style="list-style-type: none"> <li>Fleet service facilities</li> <li>In-plant large runs</li> <li>Large volume lubricant transfer</li> <li>Mining remote fill</li> </ul>	9,072 kg (> 20,000 lbs)	3/4 in NPT(F)	1-1/2 in NPT(M)	0-100 psi (0-7 bar)	Stand Mount with DataTrak	247979 – STK *312376
<b>Check-Mate 14:1</b> 	<ul style="list-style-type: none"> <li>Fleet service facilities</li> <li>In-plant large runs</li> <li>Large volume lubricant transfer</li> <li>Mining remote fill</li> </ul>	9,072 kg (> 20,000 lbs)	3/4 in NPT(F)	1-1/2 in NPT(M)	0-100 psi (0-7 bar)	Stand Mount without DataTrak	24E006 – STK *312376
<b>Check-Mate 26:1</b> 	<ul style="list-style-type: none"> <li>Fleet service facilities</li> <li>In-plant large runs</li> <li>Large volume lubricant transfer</li> <li>Mining remote fill</li> </ul>	9,072 kg (> 20,000 lbs)	3/4 NPT(F)	1-1/2 in NPT(M)	0-100 psi (0-7 bar)	Stand Mount without DataTrak	24E007 – STK *312376
<b>Check-Mate 29:1</b> 	<ul style="list-style-type: none"> <li>Fleet service facilities</li> <li>In-plant large runs</li> <li>Large volume lubricant transfer</li> <li>Mining remote fill</li> </ul>	9,072 kg (> 20,000 lbs)	3/4 in NPT(F)	1-1/2 in NPT(M)	0-100 psi (0-7 bar)	Stand Mount without DataTrak	24E008 – STK *312376
<b>Check-Mate 55:1</b> 	<ul style="list-style-type: none"> <li>Fleet service facilities</li> <li>In-plant large runs</li> <li>Large volume lubricant transfer</li> <li>Mining remote fill</li> </ul>	9,072 kg (> 20,000 lbs)	3/4 NPT(F)	1-1/2 in NPT(M)	0-100 psi (0-7 bar)	Stand Mount without DataTrak	24E009 – STK *312376
<b>Check-Mate 63:1</b> 	<ul style="list-style-type: none"> <li>Fleet service facilities</li> <li>In-plant large runs</li> <li>Large volume lubricant transfer</li> <li>Mining remote fill</li> </ul>	9,072 kg (> 20,000 lbs)	3/4 in NPT(F)	1-1/2 in NPT(M)	0-100 psi (0-7 bar)	Stand Mount without DataTrak	24E010 – STK *312376
<b>Check-Mate 68:1</b> 	<ul style="list-style-type: none"> <li>Fleet service facilities</li> <li>In-plant large runs</li> <li>Large volume lubricant transfer</li> <li>Mining remote fill</li> </ul>	9,072 kg (> 20,000 lbs)	3/4 NPT(F)	1-1/2 in NPT(M)	0-100 psi (0-7 bar)	Stand Mount without DataTrak	24E011 – STK *312376

\*Manual Number

STK – Stocked item in local warehouse

NSA – Non-stocked item that will be delivered to local warehouse by air freight

NSO – Non-stocked item that will be delivered to local warehouse by ocean freight

## Grease Pump Packages

### 35 LB & 400 LB GREASE PACKAGES



Package Number	24J030	24J042	24J066
Description	Kit 35# Drum NPT	Kit 400# Drum NPT	Kit 400# Cart with Reel NPT
Ratio	50:1	50:1	50:1
Type of Package	Stationary	Stationary	Stationary
Container Size	16 kg (35 lb)	180 kg (400 lb)	180 kg (400 lb)
Pump Part Number	24G600	24G606	24G606
Hose Kit	24H862	24H862	24J501
Hose Sizes	Grease 1.8 m (1/4 in ID x 6 ft) Air/Water 1.8 m (3/8 in ID x 6 ft)	Grease 1.8 m (1/4 in ID x 6 ft) Air/Water 1.8 m (3/8 in ID x 6 ft)	Grease 1.8 m (1/4 in ID x 6 ft) Air/Water 1.8 m (3/8 in ID x 6 ft)
LDX Hose Reel			HEH006
Follower Plate	24F901	24F903	24F903
Drum Cover	24F904	24F906	24F906
Grease Valve	242056	129581	129581
Z-Swivel	202577	129591	129591
Cart			24F915
Additional Parts			100057 Screw 100527 Washer, 111040 Nylock Nut 150287 Coupling Pipe, 1/4 x 3/8 in
Instruction Manual	3A1335	3A1335	3A1335










# DISPENSE METERS





## Graco Dispense Meters

	Fluid	Manual/ Preset	Maximum Working Pressure	Maximum Flow Rate	Intended Use	Extension	Inlet inc (mm)	Part Number
<b>EM Series Electronic Meters</b> 	Oil Anti-freeze	Manual	1,500 psi (103.4 bar)	20 gpm (76 lpm)	Indoor/ Outdoor	Flex Rigid	1/2 (13) NPT	EM8 25C904 – STK 25C903 – STK
						Flex Rigid	3/4 (19) NPT	EM20 25C918 – STK 25C919 – STK
<b>PM Series Electronic Meters</b> 	Petroleum and synthetic-based oils (motor, gear and ATF) Antifreeze	Preset	1,500 psi (103.4 bar)	20 gpm (76 lpm)	Indoor/ Outdoor	Flex	1/2 (13) NPT	PM8 273157 – STK
						Rigid		273156 – STK 25U085 – STK
						Rigid	3/4 (19) NPT	PM20 273167 – STK
						Flex		273168 – STK
<b>SD Series Electronic Meters</b> 	Oil	Manual/ Preset	1,500 psi (103.4 bar)	14 gpm (53 lpm)	Indoor/ Limited Outdoor	Flex Rigid	1/2 (13) NPT	26C354 – STK 26C384 – STK
						Flex Rigid	3/4 (19) NPT	26C361 – STK 26C360 – STK
<b>IM20 In-Line Meters</b> 	Oil Anti-freeze	In-Line	1,500 psi (103.4 bar)	20 gpm (76 lpm)	Indoor/ Outdoor		3/4 (19) NPT	25C841 – STK
<b>IM20P In-Line Meter</b> 	Petroleum and synthetic-based oils (motor, gear and ATF) Antifreeze	In-Line	1,500 psi (103.4 bar)	20 gpm (76 lpm)	Indoor/ Outdoor		1/2 (13) NPT	133480 – NSA
<b>SDV15 Control Valves</b> 	Oil Anti-freeze	N/A	1,500 psi (103.4 bar)	15 gpm (56.8 lpm)	Indoor/ Outdoor	Flex Rigid	1/2 (13) NPT	247713 – STK 247712 – STK
<b>XDV20 Control Valves</b> 	Oil Anti-freeze	N/A	1,500 psi (103.4 bar)	20 gpm (76 lpm)	Indoor/ Outdoor	Rigid	1/2 (13) NPT 3/4 (19) NPT	247718 – NSA 247722 – STK
						Flex	1/2 (13) NPT 3/4 (19) NPT	247721 – STK 247723 – STK

STK – Stocked item in local warehouse

NSA – Non-stocked item that will be delivered to local warehouse by air freight

NSO – Non-stocked item that will be delivered to local warehouse by ocean freight



Rigid



Flex

# HOSE REELS



## Hose Reels Overview

	Typical Application	Typical Fluid	Hose/Cord Length Options	Enclosed
<b>LDX™ Series</b> 	<ul style="list-style-type: none"> <li>• Small maintenance shops</li> <li>• Tire maintenance shops</li> <li>• Small fast lubes</li> <li>• Independent repair facilities</li> <li>• Industrial manufacturing facilities</li> </ul>	<ul style="list-style-type: none"> <li>• Petroleum- and synthetic-based oils</li> <li>• Air</li> <li>• Water</li> <li>• Grease</li> <li>• Antifreeze</li> <li>• Windshield washer fluid</li> <li>• Diesel exhaust fluid (DEF)</li> </ul>	<ul style="list-style-type: none"> <li>• 14 m (45 ft) – DEF only</li> <li>• 15 m (50 ft)</li> </ul>	No
<b>SDX™ 10 / 20 Series</b> 	<ul style="list-style-type: none"> <li>• Car dealerships</li> <li>• Light-/medium-duty truck dealers</li> <li>• Fleet maintenance</li> <li>• Public works garages</li> <li>• Construction vehicle maintenance</li> <li>• Light-utility service trucks</li> </ul>	<ul style="list-style-type: none"> <li>• Petroleum- and synthetic-based oils</li> <li>• Air</li> <li>• Water</li> <li>• Grease</li> <li>• Antifreeze</li> <li>• Windshield washer fluid</li> </ul>	<ul style="list-style-type: none"> <li>• 11 m (35 ft)</li> <li>• 15 m (50 ft)</li> <li>• 20 m (65 ft)</li> </ul>	Optional
<b>DXD™ 10 / 20 Series</b> 	<ul style="list-style-type: none"> <li>• Heavy-duty truck dealers</li> <li>• Fleet maintenance</li> <li>• Mining maintenance</li> <li>• Public works garage</li> <li>• Construction vehicle maintenance</li> <li>• Heavy-duty mobile service trucks</li> <li>• Mining</li> <li>• Lube trucks</li> </ul>	<ul style="list-style-type: none"> <li>• Petroleum- and synthetic-based oils</li> <li>• Air</li> <li>• Water</li> <li>• Grease</li> <li>• Antifreeze</li> <li>• Windshield washer fluid</li> </ul>	<ul style="list-style-type: none"> <li>• 11 m (35 ft)</li> <li>• 15 m (50 ft)</li> <li>• 20 m (65 ft)</li> </ul>	Optional
<b>XD™ 30 Series</b> 	<ul style="list-style-type: none"> <li>• Heavy-duty truck dealers</li> <li>• Fleet maintenance</li> <li>• Mining maintenance</li> <li>• Public works garage</li> <li>• Construction vehicle maintenance</li> <li>• Heavy-duty mobile service trucks</li> <li>• Mining</li> <li>• Lube trucks</li> </ul>	<ul style="list-style-type: none"> <li>• Petroleum- and synthetic-based oils</li> <li>• Diesel fuel</li> <li>• Air</li> <li>• Water</li> <li>• Grease</li> <li>• Antifreeze</li> <li>• Windshield washer fluid</li> <li>• Pressure wash</li> <li>• Waste oil evacuation</li> <li>• Diesel exhaust fluid (DEF)</li> </ul>	<ul style="list-style-type: none"> <li>• 11 m (35 ft)</li> <li>• 15 m (50 ft)</li> <li>• 20 m (65 ft)</li> <li>• 23 m (75 ft)</li> </ul>	No
<b>XD™ 40 / 50 Series</b> 	<ul style="list-style-type: none"> <li>• Heavy-duty truck dealers</li> <li>• Fleet maintenance</li> <li>• Mining maintenance</li> <li>• Public works garages</li> <li>• Construction vehicle maintenance</li> <li>• Heavy-duty mobile service trucks</li> <li>• Agriculture</li> <li>• Lube trucks</li> </ul>	<ul style="list-style-type: none"> <li>• Petroleum- and synthetic-based oils</li> <li>• Diesel fuel</li> <li>• Air</li> <li>• Water</li> <li>• Antifreeze</li> <li>• Waste oil evacuation</li> </ul>	<ul style="list-style-type: none"> <li>• 11 m (35 ft)</li> <li>• 15 m (50 ft)</li> <li>• 23 m (75 ft)</li> <li>• 30 m (100 ft)</li> </ul>	No
<b>XD™ 60 / 70 / 80 Series</b> 	<ul style="list-style-type: none"> <li>• Heavy-duty truck dealers</li> <li>• Fleet maintenance</li> <li>• Mining maintenance</li> <li>• Public works garages</li> <li>• Construction vehicle maintenance</li> <li>• Heavy-duty mobile service trucks</li> <li>• Agriculture</li> <li>• Lube trucks</li> </ul>	<ul style="list-style-type: none"> <li>• Petroleum- and synthetic-based oils</li> <li>• Diesel fuel</li> <li>• Air</li> <li>• Water</li> <li>• Grease</li> <li>• Waste oil evacuation</li> </ul>	<ul style="list-style-type: none"> <li>• 15 m (50 ft)</li> <li>• 23 m (75 ft)</li> <li>• 30 m (100 ft)</li> <li>• 46 m (150 ft)</li> </ul>	No

Other colours available



## Hose Reels Selection Guide

### LDX SERIES HOSE REELS


#### LDX REELS

Part Number	Fluid	Hose		Connection Size		Maximum Pressure PSI
		ID (in)	Length (ft)	Inlet (in)	Outlet (in)	
HEL010	Air/Water/Antifreeze/Windshield Washer Fluid	3/8	50	3/8 NPT	3/8 NPT	300
HEL015	DEF	1/2	45	1/2 NPT	1/2 NPT	150
HEM004	Oil	1/2	50	1/2 NPT	1/2 NPT	1,500
HEH006	Grease	3/8	50	3/8 NPT	3/8 NPT	4,060

### SDX SERIES HOSE REELS

#### ARM IN OVERHEAD MOUNT POSITION


Assembled with hose, ball stop kit and roller guide. **Required hose inlet kit sold separately.**

	Reel Size	Fluid	Hose		Connection Size		Maximum Pressure psi (bar)	Assembly Part Number	Recommended Hose Inlet Kit
			ID mm (in)	Length m (ft)	Inlet mm (in)	Outlet mm (in)			
	SDX 10	Air/Water/ Antifreeze/ Windshield Washer Fluid	10 (3/8)	11 (35)	13 (1/2)	10 (3/8)	300 (20.7)	SDL23#	218549
			10 (3/8)	15 (50)	13 (1/2)	10 (3/8)	300 (20.7)	SDL25#	
			13 (1/2)	11 (35)	13 (1/2)	13 (1/2)	300 (20.7)	SDL33#	
	SDX 20		10 (3/8)	20 (65)	13 (1/2)	10 (3/8)	300 (20.7)	SDL56#	
			13 (1/2)	15 (50)	13 (1/2)	13 (1/2)	300 (20.7)	SDL65#	
	SDX 10	Oil	13 (1/2)	11 (35)	13 (1/2)	13 (1/2)	2,000 (138)	SDM33#	218550
	SDX 20		13 (1/2)	15 (50)	13 (1/2)	13 (1/2)	2,000 (138)	SDM65#	
	SDX 10	Grease	6 (1/4)	15 (50)	10 (3/8)	6 (1/4)	5,000 (345)	SDH15#	
SDX 20	10 (3/8)		11 (35)	10 (3/8)	6 (1/4)	4,800 (331)	SDH23#		
	10 (3/8)		15 (50)	10 (3/8)	6 (1/4)	4,800 (331)	SDH55#		

### SD SERIES HOSE REELS

#### ARM IN OVERHEAD MOUNT POSITION

Assembled with hose, ball stop kit and roller guide. **Required hose inlet kit sold separately.**

	Reel Size	Fluid	Hose		Connection Size		Maximum Pressure psi (bar)	Assembly Part Number	Recommended Hose Inlet Kit
			ID mm (in)	Length m (ft)	Inlet mm (in)	Outlet mm (in)			
	SD 20	Air/Water	13 (1/2)	15 (50)	13 (1/2)	13 (1/2)	300 (20.7)	25P957	218549
		Oil	13 (1/2)	15 (50)	13 (1/2)	13 (1/2)	2,000 (138)	25P962	
		Grease	10 (3/8)	15 (50)	10 (3/8)	6 (1/4)	4,800 (331)	25P968	218550

SD Series: SDL23# A = White, B = Blue

Note: Other colours available refer to catalogue 303245


## Hose Reels Selection Guide

### XDX SERIES HOSE REELS

#### XD MODELS (WITH ADJUSTABLE ARM)


##### Reel Assemblies

Assembly includes hose, ball stop kit and roller guide. **Required hose inlet kit sold separately.**

	Reel Size	Fluid	Hose (Included)		Connection Size		Maximum Pressure psi (bar)	Recommended Hose Inlet Kit	Assembly Part Number
			ID mm (in)	Length m (ft)	Inlet	Outlet			
	XDX 10	Air/Water/Antifreeze/ Windshield Washer Fluid	10 (3/8)	15 (50)	1/2 NPSM(M)	3/8 NPT(M)	300 (20.7)	218549	XDL25#
			13 (1/2)	11 (35)	1/2 NPSM(M)	1/2 NPT(M)	300 (20.7)		XDL33#
		Oil	13 (1/2)	11 (35)	1/2 NPSM(M)	1/2 NPT(M)	2,000 (138)	218550	XDM33#
		Grease	6 (1/4)	15 (50)	3/8 NPSM(M)	1/4 NPT(M)	5,000 (552)		XDH15#
	XDX 20	Air/Water/Antifreeze/ Windshield Washer Fluid	10 (3/8)	20 (65)	1/2 NPSM(M)	3/8 NPT(M)	300 (20.7)	218549	XDL56#
			13 (1/2)	15 (50)	1/2 NPSM(M)	1/2 NPT(M)	300 (20.7)		XDL65#
		Oil	13 (1/2)	15 (50)	1/2 NPSM(M)	1/2 NPT(M)	2,000 (138)	218550	XDM65#
		Grease	10 (3/8)	15 (50)	3/8 NPSM(M)	1/4 NPT(M)	4,800 (331)		XDH55#


##### BARE REELS\*

**Required hose inlet kit sold separately.** Fluid hose not included.

	Reel Size	Fluid	Hose (Not Included)		Connection Size		Maximum Pressure psi (bar)	Recommended Hose Inlet Kit	Part Number
			ID mm (in)	Length m (ft)	Inlet	Outlet			
	XDX 10	Air/Water/Antifreeze/ Windshield Washer Fluid	10 (3/8)	20 (65)	1/2 NPSM(M)	3/8 NPSM(F)	300 (20.7)	218549	XDL2D#*
		Oil	13 (1/2)	11 (35)	1/2 NPSM(M)	1/2 NPSM(F)	2,000 (138)		XDM3B#*
		Grease	10 (3/8)	11 (35)	3/8 NPSM(M)	3/8 NPSM(F)	8,000 (552)	218550	XDH1D#*
	XDX 20	Air/Water/Antifreeze/ Windshield Washer Fluid	13 (1/2)	15 (50)	1/2 NPSM(M)	1/2 NPSM(F)	300 (20.7)	218549	XDL6D#*
		Oil	13 (1/2)	15 (50)	1/2 NPSM(M)	1/2 NPSM(F)	2,000 (138)		XDM6D#*
		Grease	10 (3/8)	15 (50)	3/8 NPSM(M)	3/8 NPSM(F)	8,000 (552)	218550	XDH5D#*

### XD 30 SERIES HOSE REELS

Recommended Reels (other reels available – see PMG Guide 303245) Includes Hose, Ball Stop, & Guide unless otherwise noted\*

	Reel Size	Fluid	Hose		Connection Size		Maximum Pressure psi (bar)	Part Number
			ID mm (in)	Length m (ft)	Inlet	Outlet		
	XD 30	Air/Water/ Antifreeze/ Windshield Washer Fluid	13 (1/2)	23 (75)	1/2 npsm(m)	1/2 npt(m)	300 (20.7)	HSLC8F
			19 (3/4)	15 (50)	3/4 npsm(m)	3/4 npt(m)	300 (20.7)	HSLD5F
		Oil	13 (1/2)	23 (75)	1/2 npsm(m)	1/2 npt(m)	1500 (103)	HSMC8F
			19 (3/4)	15 (50)	3/4 npsm(m)	3/4 npt(m)	1250 (86)	HSMDD5B HSMDD5F
			19 (3/4)	15 (50)	3/4 npsm(m)	3/4 npt(f)	2000 (138)	HSMDDA* HSMDDF*
		Grease	13 (1/2)	15 (50)	1/2 npsm(m)	1/2 npt(m)	5,000 (345)	HSHC5F
			13 (1/2)	15 (50)	1/2 npsm(m)	1/2 npt(f)	5,000 (345)	HSHCDF*
		Pressure Wash	9.5 (3/8)	23 (75)	1/2 npsm(m)	3/8 npt(m)	4,000 (276)	HSPB8F
		Fuel/Evacuation	25 (1)	9 (30)	3/4 npsm(m)	1 npt(m)	125 (8.6)	HSLE3F

\*Bare reel

XDX 10/20 Series: XDH5D# A = White, B = Blue F = Yellow


Note: Other colours available refer to catalogue 303245



## Hose Reels Selection Guide

### XD 40/50 SERIES HOSE REELS

Recommended Reels (other reels available – see PMG Guide 303245) Includes Hose, Ball Stop, & Guide unless otherwise noted\*



Other colours available

Reel Size	Fluid	Hose		Connection Size		Maximum Pressure psi (bar)	Assembly Part Number – Yellow
		ID mm (in)	Length m (ft)	Inlet NPT(F)	Outlet NPT(M)		
XD 40	Air/Water/Anti-Freeze/ Windshield Washer Fluid	19 (3/4)	30 (100)	1 npt(f)	3/4 npt(m)		24P334
		13 (1/2) 19 (3/4) 25 (1)	30 (100) 23 (75) 15 (50)	1 npt(f)	1 npt(f)	600 (41)	24P315*
		25 (1)	15 (50)	1 npt(f)	1 npt(m)	300 (21)	24P337
		19 (3/4)	30 (100)	1 npt(f)	1 npt(f)	600 (41)	24P318*
XD 50		25 (1)	30 (100)	1 npt(f)	1 npt(m)	300 (21)	24P474
XD 40	Oil	19 (3/4)	30 (100)	1 npt(f)	3/4 npt(m)	1,500 (103)	24P346
		25 (1)	15 (50)	1 npt(f)	1 npt(m)	1,275 (88)	24P349
		25 (1) 19 (3/4)	15 (50) 23 (75)	1 npt(f)	1 npt(f)	2,000 (138)	24P322*
		13 (1/2) 19 (3/4)	30 (100)	1 npt(f)	1 npt(f)	2,000 (138)	24P325*
XD 50		25 (1)	23 (75)	1 npt(f)	1 npt(m)	1,275 (88)	24P477
		25 (1)	23 (75)	1 npt(f)	1 npt(f)	2,000 (138)	24P459*
XD 40	Fuel	25 (1)	15 (50)	1 npt(f)	1 npt(m)	250 (17)	24P355
		25 (1)	15 (50)	1 npt(f)	1 npt(f)	600 (41)	24P318*
XD 50		25 (1)	30 (100)	1 npt(f)	1 npt(m)	250 (17)	24P489
		28 (1 1/2)	15 (50)	1 1/2 npt(f)	1 1/2 npt(m)	150 (10)	24P498
		32 (1 1/4)	15 (50)	1 1/2 npt(f)	1 1/2 npt(f)	600 (41)	24P462*
		38 (1 1/2)	15 (50)	1 1/2 npt(f)	1 1/2 npt(f)	600 (41)	24P468*
XD 40	Waste Oil Evacuation	1	23 (73)	1 npt(f)	1 npt(f)	600 (41)	24P318*
XD 50		32 (11/4)	15 (50)	1 1/2 npt(f)	1 1/2 npt(f)	600 (41)	24P462*

\*Bare reel


Other colours available refer to catalogue 303245

## Powered Reels Selection Guide

### Reel Frames Only




#### XD 60 / XD 70 / XD 80 Hose Reels

Motor is not included and must be purchased separately.




	Reel Size	Fluid	Hose Capacity of Reel m (ft)					Maximum Pressure psi (bar)	Weight lb (kg)	Inlet/ Outlet Size F(NPT)	Part Number – Yellow
			Hose ID in (mm)								
			13 (1/2)	19 (3/4)	25 (1)	38 (1-1/2)	51 (2)				
	XD 6010	Air/Water/ Diesel Fuel	30 (100)	30 (100)	15 (50)	–	–	600 (41)	87 (39)	25 mm/25 mm (1 in/1 in)	24T105
		Oil	30 (100)	30 (100)	15 (50)	–	–	3,000 (207)	88 (40)		24T108
		Waste Oil Evac.	–	–	15 (50)	–	–	600 (41)	87 (39)		24T105
		Grease	–	–	15 (50)	–	–	3,000 (207)	88 (40)		24T108
XD 7010	Air/Water/ Diesel Fuel	–	–	30 (100)	–	–	600 (41)	86 (39)	24T111		
	Oil	–	–	30 (100)	–	–	3,000 (207)	87 (39)	24T114		
XD 8010	Air/Water/ Diesel Fuel	–	–	46 (150)	–	–	600 (41)	127 (58)	24T123		
	Oil	–	–	46 (150)	–	–	3,000 (207)	129 (58)	24T126		
XD 7015	Waste Oil Evac.	–	–	–	15 (50)	–	600 (41)	87 (39)	38 mm/38 mm (1-1/2 in/1-1/2 in)	24T117	
	Diesel Fuel	–	–	–	20 (65)	–	600 (41)	87 (39)		24T117	
XD 8015		–	–	–	30 (100)	–	600 (41)	129 (58)		24T129	
XD 7020		–	–	–	–	10 (33)	600 (41)	91 (41)	51 mm/51 mm (2 in/2 in)	24T120	
XD 8020		–	–	–	–	15 (50)	600 (41)	133 (60)		24T132	




### Motor Assemblies – Pair with Frame-Only Models

	Part Number	Description
	24T892	Pneumatic motor assembly, reversible type. For installing motor to bare XD reel.
	24T891	Hydraulic motor assembly, reversible type. For installing motor to bare XD reel.
	24T888	24 VDC, 1/2 HP motor assembly, reversible type. For installing motor to bare XD frame.


### Ball Stop Kits

	Part Number	Description
	237873	Ball stop kit used for 3/4 in (19 mm) hose
	237874	Ball stop kit used for 1 in (25 mm) hose
	24R060	Ball stop kit used for 1.25 in (32 mm) hose
	24R061	Ball stop kit used for 1.5 in (38 mm) hose

### Hose Guide

	Part Number	Description
	24T327	Stainless steel hose guide for XD 60
	24T328	Stainless steel hose guide for XD 70
	24T329	Stainless steel hose guide for XD 80
	24R072	Roller guide kit with bracket for XD 40 and XD 60
	24T330	Roller guide kit with bracket for XD 70
	24T331	Roller guide kit with bracket for XD 80
	127271	Pneumatic valve to control XD 60/70/80 pneumatic powered hose reels. 2-position, 3-way valve.

# ELECTRIC TRANSFER PUMPS



## EGP™ Transfer and EGP On-Demand



	EGP Transfer Pump Models		EGP On-Demand Pump Models
Package Part Number	25T819	25T821	–
Pump Part Number	–	–	25T818
Voltage	12 VDC	230 VAC	12 VDC
Hertz	–	50 Hz	–
Motor Type	TENV	ODP	TENV
Horsepower	1/2	1/2	3/4
Maximum Current (Amps)	30	4.4	60
Maximum Free Flow Rate gpm (lpm)	3.8 (14.4)	3.2 (12.1)	3.8 (14.4)
Maximum Pressure psi (bar)	65 (4.5)	65 (4.5)	325 (22.4)
Automatic Relief Setting psi (bar)	65 (4.5)	65 (4.5)	325 (22.4)
Inlet	1 in NPT	1 in NPT	3/4 in NPT
Outlet	3/4 in NPT	3/4 in NPT	1/2 in NPT
Bung Adapter	260061		
Dispense Kit	133376		–
Suction Kit	133375		–
Wetted Parts	Carbon steel with zinc plating, stainless steel, galvanized steel, aluminum, nitrile, rubber, PVC, PVC cement		Carbon steel with zinc plating, stainless steel, galvanized steel, aluminum, nitrile, rubber
Weight kg (lb)	11 (25)	11 (25)	16.3 (36)
Manual	3A8569	3A8568	3A8571

Note: Cable not included

# HUSKY PUMPS





## Diaphragm Pump Selection Guide



Husky Series	Description	Part No.	Airmotor	Manifolds	Seats	Balls	Diaphragms	Typical Application
	Husky 3300 3"	652134	Aluminium	Aluminium ANSI/Flange/BSPT	Geolast	Geolast	Geolast	Waste Oil, Diesel, etc same as Buna good abrasion resistance
	Husky 3300 3"	652090	Aluminium	Aluminium ANSI/Flange/BSPT	TPE	Acetal	TPE	Hot Oil, Unleaded Fuel, Coolant typical lube application
	Husky 3300 3"	652423	Poly	Aluminium ANSI/Flange/BSPT	Santoprene	Santoprene	Santoprene	Chemical – Highest Diaphragm life where Santoprene is required
	Husky 3300 3"	652404	Poly	Poly/ANSI/DIN	Poly	PTFE	PTFE	Chemical Resistance where PTFE is required
	Husky 3300 3"	652856	Poly	Poly/ANSI/DIN	S/S	PTFE	PTFE	Highest Chemical Resistance where PTFE/Stainless is required
	Husky 2200 2"	653504	Poly	Centre Poly ANSI Flange	Poly	PTFE	PTFE	Highest Chemical Resistance where PTFE is required
	Husky 2200 2"	653511	Poly	End Poly ANSI Flange	Poly	PTFE	PTFE	Highest Chemical Resistance where PTFE is required
	Husky 2200 2"	653500	Poly	Centre Poly ANSI Flange	Poly	Santoprene	Santoprene	Chemical – Highest Diaphragm life where Santoprene is required
	Husky 2200 2"	653507	Poly	End Poly ANSI Flange	Poly	Santoprene	Santoprene	Chemical – Highest Diaphragm life where Santoprene is required
	Husky 2150 2"	DF3525	Aluminium	Aluminium NPT	TPE	Acetal	TPE	Oil, Hot Oil, Unleaded Fuel, Coolant typical Lube application
	Husky 2150 2"	DFC525	Aluminium	Aluminium BSP	TPE	Acetal	TPE	Oil, Hot Oil, Unleaded Fuel, Coolant typical Lube application
	Husky 2150 2"	DF3GGG	Aluminium	Aluminium NPT	Geolast	Geolast	Geolast	Waste Oil, Diesel etc same as Buna good abrasion resistance
	Husky 2150 2"	DFCGGG	Aluminium	Aluminium BSP	Geolast	Geolast	Geolast	Waste Oil, Diesel etc same as Buna good abrasion resistance
	Husky 15120 1.5"	654504	Poly	Centre Poly ANSI Flange	Poly	PTFE	PTFE	Highest Chemical Resistance where PTFE is required
	Husky 15120 1.5"	654511	Poly	End Poly ANSI Flange	Poly	PTFE	PTFE	Highest Chemical Resistance where PTFE is required
	Husky 15120 1.5"	654500	Poly	Centre Poly ANSI Flange	Poly	Santoprene	Santoprene	Chemical – Highest Diaphragm life where Santoprene is required
	Husky 15120 1.5"	654507	Poly	End Poly ANSI Flange	Poly	Santoprene	Santoprene	Chemical – Highest Diaphragm life where Santoprene is required
	Husky 1590 1.5"	DB3525	Aluminium	Aluminium NPT	TPE	Acetal	TPE	Oil, Hot Oil, Unleaded Fuel, Coolant typical Lube application
	Husky 1590 1.5"	DBC525	Aluminium	Aluminium BSP	TPE	Acetal	TPE	Oil, Hot Oil, Unleaded Fuel, Coolant typical Lube application
	Husky 1590 1.5"	DB3GGG	Aluminium	Aluminium NPT	Geolast	Geolast	Geolast	Waste Oil, Diesel etc same as Buna good abrasion resistance
	Husky 1590 1.5"	DBC525	Aluminium	Aluminium BSP	Geolast	Geolast	Geolast	Waste Oil, Diesel etc same as Buna good abrasion resistance
	Husky 1050 1"	647666	Aluminium	Aluminium NPT	TPE	Acetal	TPE	Oil, Hot Oil, Unleaded Fuel, Coolant typical Lube application
	Husky 1050 1"	647097	Aluminium	Aluminium BSP	TPE	Acetal	TPE	Oil, Hot Oil, Unleaded Fuel, Coolant typical Lube application
	Husky 1050 1"	647040	Aluminium	Aluminium NPT	Geolast	Geolast	Geolast	Waste Oil, Diesel etc same as Buna good abrasion resistance
	Husky 1050 1"	647121	Aluminium	Aluminium BSP	Geolast	Geolast	Geolast	Waste Oil, Diesel etc same as Buna good abrasion resistance
	Husky 1050 1"	649006	Poly	Centre Poly ANSI Flange	Poly	PTFE	PTFE	Highest Chemical Resistance where PTFE is required
	Husky 1050 1"	649034	Poly	End Poly ANSI Flange	Poly	PTFE	PTFE	Highest Chemical Resistance where PTFE is required
	Husky 1050 1"	649001	Poly	Centre Poly ANSI Flange	Poly	Santoprene	Santoprene	Chemical – Highest Diaphragm Life where Santoprene is required
	Husky 1050 1"	649029	Poly	End Poly ANSI Flange	Poly	Santoprene	Santoprene	Chemical – Highest Diaphragm Life where Santoprene is required
	Husky 1050 HP	24W764/5	Aluminium	Aluminium NPT/BSPT	Geolast	Geolast	Buna	Chemical – Highest Diaphragm Life where Santoprene is required Waste Oil – Diesel – No Unleaded Fuel General Transfer
	Husky 716 3/4"	D53277	Aluminium	Aluminium NPT	Acetal	Buna	Buna	Oil, Waste Oil, Diesel, Coolant Typical Lube application. No ULP
	Husky 716 3/4"	D5C277	Aluminium	Aluminium BSP	Acetal	Buna	Buna	Oil, Waste Oil, Diesel, Coolant Typical Lube application. No ULP
	Husky 515 1/2"	D52966	Poly	Poly NPT	Poly	Santoprene	Santoprene	Chemical – Highest Diaphragm Life where Santoprene is required
	Husky 515 1/2"	D5B966	Poly	Poly BSP	Poly	Santoprene	Santoprene	Chemical – Highest Diaphragm Life where Santoprene is required
	Husky 515 1/2"	D55A11	Poly	Poly NPT	PVDF	PTFE	PTFE	Chemical – Highest Diaphragm Life where Santoprene is required
	Husky 515 1/2"	D5EA11	Poly	Poly BSP	PVDF	PTFE	PTFE	High Chemical Resistance where PVDF/PTFE is required
	Husky 515 1/2"	D51277	Poly	Poly NPT	Poly	Buna	Buna	High Chemical Resistance where PVDF/PTFE is required Oil, Waste Oil, Diesel, Coolant Typical Lube application. No ULP
	Husky 205 1/4"	D12096	Poly	Poly NPT/BSP	Check Valve	Check Valve	Santoprene	Chemical – Highest Diaphragm Life where Santoprene is required
	Husky 205 1/4"	D12091	Poly	Poly NPT/BSP	Check Valve	Check Valve	PTFE	Highest Chemical Resistance where PTFE/Poly is required
	Husky 205 1/4"	D150A1	Poly	PVDF NPT/BSP	Check Valve	Check Valve	PTFE	Highest Chemical Resistance where PTFE/PVDF is required
	Husky 205 1/4"	D11021	Poly	Acetal NPT/BSP	Check Valve	Check Valve	PTFE	Highest Chemical Resistance where PTFE is required


### Quick Links

Sales Book: <https://salesbook.graco.com/>

Selector Tool: <https://www.graco.com/au/en/in-plant-manufacturing/support/tools/husky-selector-tool.html>

Chemical Compatibility Selector: <https://www.graco.com/au/en/in-plant-manufacturing/support/tools/chemical-compatibility.html>

# QUANTM PUMPS



## Quantm Common Pumps & Applications

Quantm Series	Part No	Pressure	Air X Ref	Loc	Manifolds	Seats	Balls	Dia	Typical Application
	TE120-0067	60 PSI	DF2911	Normal	End Poly Flange	Poly	PTFE	PTFE	Highest Chemical Resistance where PTFE is required
	TE120-0077	60 PSI	DF2966	Normal	End Poly Flange	Poly	Santo	Santo	Chemical - Highest Diaphragm Life where Santoprene can be used instead of PTFE
	TE120-0103	60 PSI	DF5A11	Normal	End PVDF Flange	PVDF	PTFE	PTFE	Highest Chemical Resistance where PVDF/PTFE is required & Poly is unacceptable
	TE120-0074	60 PSI	DFC311	Normal	Aluminium BSP	SS	PTFE	PTFE	Non Hazardous Location verify Elastomers/Manifolds chemical compatibility
	TE120-0200	60 PSI	DFC311	Haz	Aluminium BSP	SS	PTFE	PTFE	IECEx db IIb T4 Gb Hazardous Location verify material chemical compatibility
	TE120-0207	60 PSI	DFC525	Haz	Aluminium BSP	TPE	Acetal	TPE	IECEx db IIb T4 Gb Hazardous Location verify material chemical compatibility
	TE120-0065	60 PSI	DFCGGG	Normal	Aluminium BSP	Geo	Geo	Geo	Non Hazardous Location verify Elastomers/Manifolds chemical compatibility
	TE120-0078	60 PSI	DFD311	Normal	Stainless Steel BSP	SS	PTFE	PTFE	Extreme Chemical Resistance where PTFE/Stainless is required
	TE120-0204	60 PSI	DFD311	Haz	Stainless Steel BSP	SS	PTFE	PTFE	IECEx db IIb T4 Gb Hazardous Location verify material chemical compatibility
	TE80-0060	100 PSI	DB2911	Normal	End Poly Flange	Poly	PTFE	PTFE	Highest Chemical Resistance where PTFE is required
	TE80-0068	100 PSI	DB2966	Normal	End Poly Flange	Poly	Santo	Santo	Chemical - Highest Diaphragm Life where Santoprene can be used instead of PTFE
	TE80-0066	100 PSI	DBC311	Normal	Aluminium BSP	SS	PTFE	PTFE	Non Hazardous Location verify Elastomers/Manifolds chemical compatibility
	TE80-0182	100 PSI	DBC311	Haz	Aluminium BSP	SS	PTFE	PTFE	IECEx db IIb T4 Gb Hazardous Location verify material chemical compatibility
	TE80-0191	100 PSI	DBC525	Haz	Aluminium BSP	TPE	Acetal	TPE	IECEx db IIb T4 Gb Hazardous Location verify material chemical compatibility
	TE80-0059	100 PSI	DBC GGG	Normal	Aluminium BSP	Geo	Geo	Geo	Non Hazardous Location verify Elastomers/Manifolds chemical compatibility
	TE80-0072	100 PSI	DBD311	Normal	Stainless Steel BSP	SS	PTFE	PTFE	Extreme Chemical Resistance where PTFE/Stainless is required
	TE80-0188	100 PSI	DBD311	Haz	Stainless Steel BSP	SS	PTFE	PTFE	IECEx db IIb T4 Gb Hazardous Location verify material chemical compatibility
	TE30-0424	100 PSI	647097	Haz	Aluminium BSP	TPE	Acetal	TPE	IECEx db IIb T4 Gb Hazardous Location verify material chemical compatibility
	TE30-0167	100 PSI	647109	Normal	Aluminium BSP	SS	PTFE	PTFE	Non Hazardous Location verify Elastomers/Manifolds chemical compatibility
	TE30-0426	100 PSI	647109	Haz	Aluminium BSP	SS	PTFE	PTFE	IECEx db IIb T4 Gb Hazardous Location verify material chemical compatibility
	TE30-0166	100 PSI	647121	Normal	Aluminium BSP	Geo	Geo	Geo	Non Hazardous Location verify Elastomers/Manifolds chemical compatibility
	TE30-0268	100 PSI	649001	Normal	Cntr Poly Flange	Poly	Santo	Santo	Chemical - Highest Diaphragm Life where Santoprene can be used instead of PTFE
	TE30-0258	100 PSI	649006	Normal	Cntr Poly Flange	Poly	PTFE	PTFE	Highest Chemical Resistance where PTFE is required
	TE30-0269	100 PSI	649029	Normal	End Poly Flange	Poly	Santo	Santo	Chemical - Highest Diaphragm Life where Santoprene can be used instead of PTFE
	TE30-0257	100 PSI	649034	Normal	End Poly Flange	Poly	PTFE	PTFE	Highest Chemical Resistance where PTFE is required
	TE30-0274	100 PSI	649384	Normal	Cntr PVDF Flange	PVDF	PTFE	PTFE	Highest Chemical Resistance where PTFE is required
	TE30-0273	100 PSI	649398	Normal	End PVDF Flange	PVDF	PTFE	PTFE	Highest Chemical Resistance where PVDF/PTFE is required & Poly is unacceptable
	TE30-0161	100 PSI	651032	Normal	Stainless Steel BSP	SS	PTFE	PTFE	Extreme Chemical Resistance where PTFE/Stainless is required
	TE30-0420	100 PSI	651032	Haz	Stainless Steel BSP	SS	PTFE	PTFE	IECEx db IIb T4 Gb Hazardous Location verify material chemical compatibility

\* For IECEx Hazardous locations Leak Detector "25F109" is recommended

## QUANTM™ ELECTRIC PUMP

### Save Energy, Cut Costs & Run Cleaner

QUANTM isn't just another electric pump: it's a game-changer. QUANTM features a revolutionary electric motor design that will reduce operational costs and keep your production lines running.

It is a perfect fit for nearly any fluid application and a drop-in replacement for existing pumping technologies.

Protect your bottom line by converting to a QUANTM Electric Pump.

#### EFFICIENT ELECTRIC DRIVE

- Up to 80% less energy consumption
- Requires no compressed air
- No freezing

#### INTEGRATED CONTROLS

- Control flow and pressure at the pump
- I/O for remote operation

#### PROVEN ADD BENEFITS

- Stalls under pressure
- Self-priming
- Dry running
- Handles solids and abrasive materials

#### PLUG & PLAY

- Factory wired for quick install
- 240V
- Hazardous Location models available



**SUSTAINABLE  
OPERATIONS**



**OPERATIONAL  
RESILIENCE**



**COST  
SAVINGS**



**SIMPLIFIED  
MAINTENANCE**





## GRACO'S GOT YOU COVERED

### FACILITIES WORLDWIDE FOR GLOBAL SUPPORT



#### Quality First

At Graco we pride ourselves on providing best-in-class products. Engineered solutions are manufactured in our own facilities, with the highest standards in the industry. We provide you with world-class customer support and expertise to help solve your lubrication challenges.



#### Global Reach

Graco has facilities across the globe to provide you with the products and service *you* need, where *you* live. Plus, Graco has dedicated field experts in all areas of the world to support the products we sell.



#### Product Capabilities

Graco has a broad range of products to provide solutions that meet your needs. Our products are engineered and tested to perform in the harshest environments so you can be certain your equipment is protected and working at peak performance.

Graco Australia Pty Ltd  
Suite 17, 2 Enterprise Drive  
Bundoora, VIC 3083  
Australia  
Tel: 61 3 9468 8500  
Fax: 61 3 9468 8599  
Email: [csaustralia@graco.com](mailto:csaustralia@graco.com)